

KLX DISSOLVABLE FRAC PLUG- SPECIALTY SIZES

The KLX Dissolvable Frac Plug is designed to meet the industry’s challenging downhole requirements for today’s completion operations. The plug has a proven track record of reliability & performance during deployment and fracturing operations.

The KLX Dissolvable Frac Plug is offered in a variety of specialty sizes to accommodate the wide scope of completion and re-frac applications. Available in a ‘Standard/Salt’ water alloy and a ‘Fast/Fresh’ water alloy, the specialty sized dissolvable plugs are a suitable option for a broad range of frac fluids & wellbore environments. The plugs come in a ‘Top Ball’ configuration.

Please contact your local KLX Sales Representative for additional technical information and plug options.

FEATURES & BENEFITS

- Available in Standard/Salt Water Alloy or Fast/Fresh Water Alloy
- Top Ball Configuration
- Robust, Optimized Design and ‘Bottom-Set’ Feature Eliminates ‘Presets’ During Plug Deployment/Pump Down Operations
- Predictable and Reliable Rate of Dissolution
- Tested & Qualified to 10,000psi up to 300°F



KLX DSV PRODUCT SPECIFICATIONS- SPECIALTY SIZES

TOOL SIZE	CASING WT. RANGE	MIN CSG ID	MAX CSG ID	PLUG OD	BALL OD	ALLOY	KLX PN
3.500"	9.2#	2.918"	3.046"	2.690"	1.875"	STANDARD	DSV-35-FPH
						FAST	DSV-35-RD
4.000"	11#	3.402"	3.530"	3.230"	2.500"	STANDARD	DSV-40-FPH
4.500" CSG PATCH	13.5# PATCH	3.321"	3.321"	3.050"	1.875"	STANDARD	DSV-45-PPH
4.500"	15.10#	3.750"	3.903"	3.600"	2.750"	STANDARD	DSV-46-FPH
						FAST	DSV-46-RD
5.000"	18#	4.195"	4.361"	4.026"		STANDARD	DSV-50-FPH
						FAST	DSV-50-RD
	21.4#	4.030"	4.218"	3.875"		STANDARD	DSV-52-FPH
						FAST	DSV-52-RD
5.500"	23-26.8#	4.393"	4.766"	4.300"		STANDARD	DSV-57-FPH



3040 Post Oak Blvd., 15th Floor
 Houston, TX 77056
 Tel 832.844.1015
klxenergy.com

NEXT LEVEL READINESS >